

MAPEPROOF FIX TAPE

Double-sided adhesive tape to hold sheets of MAPEPROOF FBT in place during installation



ADVANTAGES

- **Mapeproof Fix Tape** is highly adhesive and holds **Mapeproof FBT** firmly in place during installation, including on vertical surfaces.
- **Mapeproof Fix Tape** is cold-applied and does not require heat and/or naked flames.
- Easy to apply: **Mapeproof Fix Tape** is extremely flexible and adhesive, even at low temperatures.

TECHNICAL CHARACTERISTICS

Mapeproof Fix Tape is double-sided adhesive tape that adheres perfectly to various types of substrate. **Mapeproof Fix Tape** is one of the accessory items used in the **Mapeproof FBT** waterproofing system.

APPLICATION PROCEDURE

Substrates must be sound and dry and have no free-standing water. The surfaces on which **Mapeproof Fix Tape** is to be applied must be even and have no large protruding areas or gaps.

Substrates suitable for applying **Mapeproof Fix Tape** include concrete, formwork, rigid insulation boards and wooden panels.

Unroll the **Mapeproof Fix Tape** and bond it to the substrate, making sure there are no folds. Then, remove the protective film and bond the sheets of **Mapeproof FBT** in place over the tape. It is important that the protective film is only removed immediately before bonding the **Mapeproof FBT** to prevent the adhesive on the **Mapeproof Fix Tape** from getting dirty from dust or other loose material.

RECOMMENDATIONS

Mapeproof Fix Tape must not be applied if there is water or puddles.

Mapeproof Fix Tape must not be exposed to UV rays for more than 4 weeks after being applied.

PACKAGING

Mapeproof Fix Tape is available in 0.20 m wide rolls x 25 metres long.

STORAGE

Mapeproof Fix Tape may be stored for 12 months in its original packaging in a dry area at a temperature of +5°C to + 35°C.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Mapeproof Fix Tape is an article that, according to current European Regulations (Reg. (EC) 1906/2007 - REACH), does not require a Safety Data Sheet. When using this product it is recommended to wear gloves and safety goggles and to follow the safety guidelines for the area in which work is carried out.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)	
PRODUCT IDENTITY	
Appearance/material:	transparent/double-sided adhesive tape
Width of roll (m):	0.20
Nominal thickness (mm):	0.61
Weight (kg/m ²):	≥ 0.67
APPLICATION DATA	
Application temperature:	+5°C to +35°C

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

7498-3-2019-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

